

imagePROGRAF
TM-200 MFP L24ei

TOP QUALITY PRINTING AND SCANNING FROM A LARGE FORMAT MFP BOASTING LUCIA TD INK

Quietly compact, the imagePROGRAF TM-200 MFP L24ei delivers high quality printing and scanning in parallel. 5-colour, full pigment Lucia TD ink prints crystal clear lines and bold colours, while SingleSensor Technology speeds up scanning.



- Less installation space is needed, thanks to the integrated design with full front usability
- Print noise is reduced by 60%, from dampened fans, fewer vibrations and streamlined cutting
- Dedicated ScanApp Lei Software, from Global Scanning, boosts productivity with continuous scan and copy to cloud, USB and PC
- Exceptional print quality for CAD and poster printing from 5-colour, full pigment Lucia TD ink
- Parallel processing means print and scan can work simultaneously, boosting office efficiency
- SingleSensor technology from Global Scanning delivers crystal clear lines and text as well as bold colours
- Enjoy effortless indoor and outdoor applications including a unique Water Resistant Media portfolio
- Ease of use can be reached by the 3-inch flat panel touchscreen display

PRODUCT RANGE



TM-200



TM-205



TM-300 MFP L36ei

Canon

TECHNICAL SPECIFICATIONS

imagePROGRAF TM-200 MFP L24ei

SCANNER TECHNOLOGY

| | |
|---|--|
| Scan technology | SingleSensor with multiple LED illumination |
| Optical resolution | 600dpi. |
| Scan speed | COPY 300/300dpi Draft = 1ips colour, 3ips mono 300/600dpi Standard = 1ips colour, 3ips mono 600/600dpi Best = 0.5ips colour, 1.5ips mono |
| Scan modes | SCAN 200dpi Draft = 1ips colour, 3ips mono 300dpi Standard = 0.5ips colour, 1.5ips mono 600dpi Best = 0.33ips colour, 1ips mono Scan to USB - RGB/Greyscale/BW, TIFF (No ScanApp Lei) Scan to USB - RGB/Greyscale/BW, JPG, PDF, PDF/A, M-PDF (ScanApp Lei available) Scan to PC - RGB/Greyscale/BW, Tiff, JPEG, PDF, PDF/A, TiffG4, M-PDF Copy - RGB/Greyscale/BW Copy & Archive - (Combination of Copy and Scan to PC above). Cloud connectivity is achieved by a link to Canon's Direct Print & Share. PRINT is achieved by using Canon's Direct Print & Share. |
| Paper Path | Face up, rear exit. Forward document transport only Document return guide(s) included |
| Scan width | 24" / 609.6mm |
| Min. scan width | 6.2" / 157.4mm |
| Max. document width | 26" / 660.4mm |
| Max. scan length | 109" / 2768mm |
| Max. & Min. document thickness | Designed to scan Canon iPF printer CAD paper. Min = 0.07mm Max = 0.5mm |
| Scan accuracy | Accuracy 0.2% +/-1 pixel |
| Scan to USB | USB2, 128GB FAT32. |
| Scan to Network - ScanApp Lei | ScanApp Lei - Sets scan directory. Minimum PC specification: • Windows 7/8/10 - 32bit. • 100Mbps Ethernet. • Intel Celeron, Core-Duo, Core-2-Duo or 2.8GHz Hyper-Threading (HT) or AMD Dual-Core processors • 2GB RAM • High speed 7,200rpm Serial ATA (SATA) HDD with minimum 2GB for applications and 20GB free for images. Suggested PC specification: • Windows 7/8/10 - 64bit. • GB Ethernet. • Intel i3,i5 or i7 processors • 4GB RAM • High speed 7,200rpm Serial ATA (SATA) HDD with minimum 2GB for applications and 20GB free for images. |
| Languages for ScanApp Lei | English/French/German/Italian/Spanish/Simplified Chinese/Traditional Chinese/Korean/Russian/Portuguese/Japanese/Czech/Polish |
| Control panel | 3" touch screen display |
| Weight of scanner | 5.28kg (11.6lbs) without Doc return guide |
| Dimensions width | 935mm |
| Dimensions height | 131mm |
| Dimension depth | Without Doc Return Guide - Paper tray folded: 146mm Without Doc Return Guide - Paper Tray flat: 193mm With Doc Return Guide - Paper tray folded: 206mm With Doc Return Guide - Paper Tray flat: 253mm |
| Power supply | External PSU: Input: 100 - 240V, 50-60Hz Output: 3.42A at 19V. |
| Max. power consumption | Standby (sleep): 0.6W Idle: 11.7W Scanning: 17.5W |
| Environmental | Temp: 10-35C Humidity: 10-90% |
| Acoustic noise levels | 48.4dB gray scan |
| Compliances | Europe : CE mark, Russia : EAC, Other countries : CB Certification |
| What's in the box? | L24ei scanner Printer mounting brackets, fixings & 3mm tool 2 feet for desktop use 2 paper edge guides 1 Document return guides Calibration target CD for ScanApp Lei software (includes PDF documentation: L24ei Scanner User Manual per language and Quick Start Guide) L24ei Scanner Quick Start Guide. Ethernet cable (2 meter) Power Supply Regional - Mains power cord(s) (2 meter) |

PRINTER TECHNOLOGY

| | |
|--------------------------|--|
| Printer Type | 5 Colour 24"/610mm |
| Print Technology | Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head) |
| Print Resolution | 2,400 x 1,200 dpi |
| Number of Nozzles | 15,360 nozzles (MBK 5,120 nozzles, Other Colours 2,560 nozzles each) |
| Line Accuracy | ±0.1% or less |
| Nozzle Pitch | 1,200 dpi (2 lines) |
| Ink Droplet Size | minimum 5 pl per colour |
| Ink Capacity | Sales Ink: 130ml/300ml Bundled Starter Ink: 130ml (Matte Black)/90ml (Black, Cyan, Magenta, Yellow) |

Ink Type

OS Compatibility

Printer Languages

Standard Interfaces

MEMORY

Standard memory

PRINTING SPEED

CAD Drawing:

Plain Paper (A1 Roll)

Poster:

Plain Paper (A1 Roll)

Heavy Coated Paper (A1 Roll)

MEDIA HANDLING

Media Feed and Output

Media Width

Media Thickness

Minimum Printable Length

Maximum Printable Length

Maximum Media Roll Diameter

Media Core Size

Margins Recommended area

Margins Printable area

Media Feed Capacity

Borderless Printing Width (Roll Only)

Maximum number of delivered prints

WHAT'S INCLUDED

What's in the Box?

Software Included

OPTIONS

Optional Items

CONSUMABLES

User Replaceable Items

Notes & Recommendations

- Note 1 Maximum number of supported printers or PCs running ScanApp Lei = 15 (Maximum number that can be assigned a number = 9).
- Note 2 Scanner is manufactured by UK based company, Global Scanning
- Note 3 Excludes strong curling conditions

Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.¹ and * All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.

Pigment inks - Black, Matte Black, Cyan, Magenta, Yellow

Microsoft Windows 32 Bit: Windows 7, 8.1, 10
Microsoft Windows 64 Bit: Windows 7, 8.1, 10, Windows Server 2008R2, Windows Server 2012/2012R2, Windows Server 2016
Apple Macintosh: OSX 10.10.5 - OSX 10.11, macOS 10.13

SG Raster (Swift Graphic Raster), HP-GL/2, HP RTL, JPEG (Ver. JFIF 1.02)

USB B Port: Built-in Hi-Speed USB
Ethernet: IEEE 802.3 1-base-T/IEEE 802.3u 100base-TX/
IEEE 802.3ab 1000base-T/IEEE 802.3x Full Duplex
Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b

2 GB

0:24 (Fast Economy Mode)
0:27 (Fast)
0:42 (Standard)

0:25 (Fast)
0:44 (Standard)

0:55 (Fast)
1:22 (Standard)

Roll paper: One Roll, Upper-loading, Front Output
Cut sheet: Upper-loading, Front Output (Manual feed using media locking lever)

Roll paper: 203.2 - 610 mm
Cut sheet: 203.2 - 610 mm

Roll/Cut: 0.07 - 0.8 mm

Roll paper: 203.2 mm
Cut sheet: 279.4 mm

Roll paper: 18 m (Varies according to the OS and application)
Cut sheet: 1.6 m

150 mm

Internal diameter of roll core: 2"/3"

Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm
Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm

Roll paper: Top: 3 mm, Bottom: 3 mm, Side: 3 mm
Roll paper (borderless): Top: 0 mm, Bottom: 0 mm, Side: 0 mm
Cut sheet for Apple AirPrint Only: Top: 3 mm, Bottom: 12.7 mm, Side: 3 mm
Cut sheet for others: Top: 3 mm, Bottom: 20 mm, Side: 3 mm

Manually switchable by user

515mm (JIS B2), 594mm (ISO A1), 10", 14", 17", 24"
[Printable] 257mm (JIS B4), 297mm (ISO A3), 329mm
(ISO A3+), 420mm (ISO A2), 8", 12", 16", 20", 300mm,
500mm, 600mm

Standard position: 1 sheet
Flat position - 20 sheets on A2 landscape ⁽³⁾

Printer, 1 x print head, 3-inch paper core attachment, Power Cable, UK Power cord (240V, 3P), 1 set of starter ink tanks, Set up guide, Safety/Standard Environment leaflet
User software CD-ROM (Win)
PosterArtist Lite CD-ROM, EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet
imagePROGRAF TM-Series Printer Driver, Print Plug-In for Office, Quick Utility Toolbox and PosterArtist Lite
Other software available as Download from Web.

2/3" Roll Holder: RH2-28
Printer Stand: SD-23

Ink Tank: PFI-120 (130ml), PFI-320 (300ml)
Print Head: PF-06
Cutter Blade: CT-08
Maintenance Cartridge: MC-31



Canon Inc.
canon.com

Canon Europe
canon-europe.com

English edition

© Canon Europa N.V., 2018